

# Encoded Universality from a Single Physical Interaction

written by J. Kempe, D. Bacon, D. P. DiVincenzo, and K. B. Whaley

presented by Ketan Patel

July 8, 2002

## Outline

- Background & Motivation
- Exchange Hamiltonian
- Encoded Universality from Isotropic Exchange Hamiltonian
- Encoded Universality from Anisotropic Exchange Hamiltonian
- Error Correction and Leakage
- Decoherence-free Subspaces
- Open Problems

## Traditional Approach to Universal Computation

- Generate Universal Gate Set  
Example: Hadamard, phase,  $\pi/8$  and C-NOT
- Find physical implementation for set

Problem: Don't always have a reliable physical implementation

## Basic Idea of "Encoded Universality"

Let  $L$  be quantum gate library that is **not** universal

Encoding qubits in larger Hilbert space & applying  $L$  may be universal in original space

## Hamiltonians and Unitary Operators

Time evolution of quantum state described by Schrödinger Equation

$$i\hbar \frac{d|\psi\rangle}{dt} = H|\psi\rangle$$

Gives unitary operator

$$U(t_1, t_2) = \exp\left[\frac{-iH(t_2 - t_1)}{\hbar}\right]$$

Given a set of primitive Hamiltonians what others can be obtained?

## Trotter and Baker-Campbell-Hausdorff Formulae

Rules for combining Hamiltonians:

$$e^{i(\alpha\mathbf{A} + \beta\mathbf{B})} = \lim_{p \rightarrow \infty} \left( e^{i\alpha\mathbf{A}/p} \cdot e^{i\beta\mathbf{B}/p} \right)^p$$

$$e^{i[\mathbf{A}, \mathbf{B}]} = \lim_{p \rightarrow \infty} \left( e^{-i\mathbf{A}/\sqrt{p}} \cdot e^{i\mathbf{B}/\sqrt{p}} \cdot e^{i\mathbf{A}/\sqrt{p}} \cdot e^{-i\mathbf{B}/\sqrt{p}} \right)^p$$

⇒ New Hamiltonians formed by linear combinations

$$\alpha\mathbf{A} + \beta\mathbf{B}$$

and Lie-commutators

$$i[\mathbf{A}, \mathbf{B}] = i(\mathbf{AB} - \mathbf{BA})$$

## Heisenberg Exchange Hamiltonian

$$H_{ij} = J_{ij}^X \sigma_x^i \sigma_x^j + J_{ij}^Y \sigma_y^i \sigma_y^j + J_{ij}^Z \sigma_z^i \sigma_z^j$$

Isotropic Case:

$$H_{ij} = J_{ij} \sum_{i \neq j} \left( \sigma_x^i \sigma_x^j + \sigma_y^i \sigma_y^j + \sigma_z^i \sigma_z^j \right)$$

Example:

$$H_{12} = J_{ij} \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & -1 & 2 & 0 \\ 0 & 2 & -1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \quad \text{Setting } J_{ij} = 1 \quad \frac{1}{2}(I + H_{12}) = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

## Encoded Universality

Isotropic exchange interaction not universal

However it is universal in a subspace

Use representation theoretic analysis to find subspace and encoding

Encoding efficiency  $\rightarrow 1$  as  $n \rightarrow \infty$

Must also introduce tensor structure

conjoining encoded qubits

## Explicit Encoding

$$|0_L\rangle = \frac{1}{\sqrt{2}}(|010\rangle - |100\rangle)$$

$$|1_L\rangle = \sqrt{\frac{2}{3}}|001\rangle - \sqrt{\frac{1}{6}}|010\rangle - \sqrt{\frac{1}{6}}|100\rangle$$

Single-qubit gates implemented with  $\leq 4$  exchange interactions  
Nontrivial two-qubit gate implemented with 19 exchange interactions

## Anisotropic Exchange Hamiltonian (XY-interaction)

$$H_{ij} = \frac{J_{ij}}{2} (\sigma_x^i \sigma_x^j + \sigma_y^i \sigma_y^j)$$

Relevant for quantum dot spins & cavity QED

Can achieve encoded universality for **qutrit** with 3 physical qubits

Explicit encoding:

$$|0_L\rangle = |100\rangle \quad |1_L\rangle = |010\rangle \quad |2_L\rangle = |001\rangle$$

## Universality Criterion

Not every physical interaction gives encoded universality

Generally must determine on case by case basis

Necessary Condition:

# of linearly independent operators in Lie algebra of  $H_n$  must  $>$   $\text{poly}(n)$

Example:

$$\{\sigma_z^i, \sigma_x^i \sigma_x^{i+1}\}$$

has no universal encoding

## Error Correction and Leakage

Standard FT procedures apply

Can be concatenated within stabilizer code

“Leakage” can be a problem

Authors give procedure for dealing with leakage

## Decoherence-Free Subspaces

Qubits encoded in subspace invariant to collective decoherence

### Example:

Collective Dephasing ( $|0\rangle \rightarrow |0\rangle$ ,  $|1\rangle \rightarrow e^{i\alpha}|1\rangle$ )

Encode Basis States  $|1\rangle \rightarrow |10\rangle$ ,  $|0\rangle \rightarrow |01\rangle$

## Open Questions/Problem

- What other interactions yield “encoded universality”?
- Affect of additional restriction on universality (e.g. only nearest neighbor interactions allowed)
- (Optimal) synthesis for encoded gates